



AIRTRAK-VET25
Ventilated Edge Trim for 25mm plywood
Supplied by Nicholson
Tel 0845 0098 980
Web www.nicholsonsts.com

Material
0.7mm stainless steel, vinyl coated GRP insect mesh


Ventilation
25mm continuous air gap equivalent

Dimensions
OA girth 100mm, length 1000mm

Compatibility
For use with 18mm and 15mm plywood

Installation
The VET Ventilator is fitted to the edge of the plywood prior to it being fixed in position into the edge of the plywood using non ferrous fixings. The lead cladding to the ventilator is welted around the edge of the ventilator to prevent wind uplift. Lengths should be butted together or lapped by 10mm if required. The ventilator can be mitred at corners and trimmed to length with a large pair of tin snips.

To specify
Airtrak VET18 Ventilated Edge Trim for 18mm plywood
Airtrak VET25 Ventilated Edge Trim for 25mm plywood



© Nicholson 2015	AIRTRAK-VET25 Ventilated Edge Trim for 25mm plywood Supplied by Nicholson Tel 0845 0098 980 Web www.nicholsonsts.com	Revision Date	Description	Drawing Purpose: Construction detail			Drawing title AIRTRAK-VET25	
Construction Risks				Drawn by	Checked by	Authorized by		
Maintenance / Cleaning risks							Scale@A3: 1:2	Drawing Number:
Demolition Adaptation Risks							Drawing Date 25th Sep 2015	Revision Date Revision