

roof void ventilation

AIRTRAK™

AIRTRAK-PE100 Pitched Eaves Ventilator

Supplied by Nicholson
Tel 0845 0098 980
Web www.nicholsonsts.com

Material
0.7mm stainless steel, vinyl coated GRP insect mesh


Ventilation
25mm continuous air gap equivalent

Dimensions
OA girth 125mm, length 1000mm

Compatibility
For providing ventilation in lead, copper, zinc, stainless steel, terne coated and aluminium membrane and liquid roof coverings

Installation
The PE100 Ventilator is fitted to a 1mm rebate in the edge of the pitched roof with non ferrous fixings and extends down over a ventilated upstand. Lengths should be butted together or lapped by 10mm if required. The ventilator can be mitred at corners and trimmed to length with a large pair of tin snips. The metal roof covering is dressed down the face of the ventilator and welted around the lower edge. For code 6 lead and above, trim the lead flush with the ventilator and use the CF Clipfast Clips to restrain against wind uplift. For membrane and liquid applied roof coverings, a suitable metal flashing material should be used to cover the ventilator welting around the lower edge and extend onto the roof to facilitate a lap joint in accordance with the manufacturers instructions.

To specify
Airtrak PE100 Pitched Eaves Ventilator for roof pitch of ____°



© Nicholson 2015	AIRTRAK-PE100 Pitched Eaves Ventilator Supplied by Nicholson Tel 0845 0098 980 Web www.nicholsonsts.com	Revision Date	Description	Drawing Purpose: Construction detail			Drawing title AIRTRAK-PE100 Pitched Eaves Ventilator.	
Construction Risks				Drawn by	Checked by	Authorized by		
Maintenance / Cleaning risks							Scale@A3: 1:2	Drawing Number:
Demolition Adaptation Risks							Drawing Date 25th Sep 2015	Revision Date Revision