

roof void ventilation

AIRTRAK™

AIRTRAK-CF

Clipfast Clip  
Supplied by Nicholson  
Tel 0845 0098 980  
Web www.nicholsonsts.com


Material  
0.5mm stainless steel or 0.6mm copper

Dimensions  
OA length 70mm, OA width 60mm

Compatibility  
Fixing clip for securing lead flashings to the Airtrak ventilators where the flashing is too thick to welt around the edge of the ventilator.

Installation  
The Airtrak ventilators are pre-slotted at approx 300mm centres to receive the CF Clipfast Clips. The CF should be dropped into the slots from the front prior to dressing the flashing over the ventilator. The flashing should be trimmed just past the bottom of the ventilator. The CF clips are then turned up over the face of the flashing and crimped with seaming pliers. Where a welled drip appearance is desired, the flashing can be welted around the lower edge of the ventilator but with a 55mm cut out where the CF clips are located.

To specify  
Airtrak CF Clipfast Clips



© Nicholson 2015	AIRTRAK-CF CLIPFAST CLIP Supplied by Nicholson Tel 0845 0098 980 Web www.nicholsonsts.com	Revision Date	Description	Drawing Purpose: Construction detail			Drawing title AIRTRAK-CF	
Construction Risks				Drawn by	Checked by	Authorized by		
Maintenance / Cleaning risks							Scale@A3: 2:1	Drawing Number:
Demolition Adaptation Risks							Drawing Date 07th July 2015	Revision Date Revision